

FLANGE DI ACCOPPIAMENTO - FLANGE YOKE


SAE


Fig. 1




Fig. 2

Fig. 3




Fig. 8


DIN


Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 9

FLANGE SPECIALI PER FUORISTRADA - FLANGE YOKE FOR 4 X 4

D x L	Applicazione	Tipo	FIG.	A	B	C	N° Fori	dB13	F	G	H	β _{max}	COD. TRASMEC
27 x 74,6 (1027)	Land Rover - Defender	SAE 1300	1	97	79,37	60,32	4	10	1,5	8	50	28°	FL 50.97.4.10
	Mercedes G - attacco Sprinter	DIN 90	4	90	47	74,5	6	10	2,5	8	50	28°	FL 50.90.6.10
	Suzuki Samurai	SAE 45	1	100	84,71	44,96	4	8,5	3	7,5	50	28°	FL 50.100.4.8
	Suzuki Jimmy	SAE 45	1	100	84,71	44,96	4	10,5	3	7,5	50	28°	FL 50.100.4.10
27 x 81,7 (1028)	Nissan Trade	SAE 65	1	120	94,92	64,98	4	12	3,2	7,8	55	28°	FL 55.120.4.12
30,2 x 81,8 (1020)	Land Rover - Defender	SAE 1300 W	1	97	79,37	60,32	4	10	1,5	8	58,5	35°	FL 58.97.4.10
	Discovery 2	SAE 65D	1	120	94,92	64,98	4	10	3,2	7,8	55	30°	FL 55.120.4.10
	Massif	SAE 1410	1	116	95,27	69,85	4	12	1,5	8	54	30°	FL 54.116.4.12
	Mercedes ML	SAE 70	1	120	95	70	4	10	3,2	8	54	30°	FL 54.119.4.10
	Mercedes Sprinter Furgone	DIN 57	4	120	101,6	57	4	10	2,8	7	54	30°	FL 54.120.4.10
	Mercedes G - attacco Sprinter	DIN 90	5	90	74,5	47	6	10	2,8	7	50	28°	FL 50.90.6.10
	Mercedes G	DIN 100	6	100	84	57	8	8	3	7	54	30°	FL 54.100.8.8
	Nissan Patrol - Y60	SAE 65	1	120	94,92	64,98	4	12	3,2	7,8	55	30°	FL 55.119.4.12
	Nissan Patrol - Y61	DIN 135	4	135	108	65	4	13	4	8	55	30°	FL 68.135.4.13
	JK Rubicon	DIN 99	6	99,8	86	-	8	9	-	1,2	54	30°	FL 54.099.8.9
	Toyota*	SAE 46	1	120	-	45,98	4	10	3,3	8	54	30°	FLX 54.120.0.0
	Toyota	SAE 46	1	120	91	45,98	4	8	3,3	8	54	30°	FLX 54.120.1.0
	Toyota	SAE 46	1	120	91	45,98	4	10	3,3	8	54	30°	FLX 54.120.1.1
	Toyota BJ 40 - KZJ 73 / 78	SAE 46	1	120	93,18	45,98	4	11	3,3	8	54	30°	FLX 54.120.1.2
	Toyota HDJ 80	SAE 45	1	130	104,5	45,00	4	12	3,3	8	54	30°	FLX 54.120.2.0
	Toyota BJ71 - HZJ71 posteriore	SAE 46	1	120	93,34	45,98	4	10	3,3	8	54	30°	FLX 54.120.1.3
	Toyota LJ70 - BJ71 - HZJ71	SAE 46	1	100	84,85	45,98	4	10	3,3	8	54	30°	FLX 54.100.1.1

*FORNITA SENZA FORI PER PERSONALIZZAZIONE